

## NOTICE TO BIDDERS

The Board of Commissioners of the Red River, Atchafalaya & Bayou Boeuf Levee District will receive sealed bids at 10 Calvert Drive, Alexandria, LA 71303 until 10:00 a.m CST Monday, March 3, 2025, for:

Two (2) New Tandem Diesel Trucks with 12-14 Cubic Yard Dump Bed

at which time bids shall be publicly opened and read aloud.

All bids shall be submitted in sealed envelopes by the vendor and marked to indicate the above item bid. Detailed specifications and proposal forms can be obtained from the Levee District office located at 10 Calvert Drive, Alexandria LA 71303 between the hours of 8:00 a.m. and 4:30 p.m., or by calling 318-443-9646, except holidays or by electronic bid at [www.centralauctionhouse.com](http://www.centralauctionhouse.com).

The specifications are used only to denote the quality standard of product desired and do not necessarily restrict bidders to a specific brand, manufacturer, or named specification. The specifications are used only to set forth and convey to prospective bidders the general style, type, character, and quality of the product desired. Equivalent or better products will be acceptable.

Prospective bidders must have a dealer certified mechanic shop capable of providing all warranty, parts and service requirements within the levee district territory as a pre-requisite to bidding.

No bid bond is required for this project.

No bidder may withdraw his bid for at least (30) days after the time scheduled for the opening of bids.

The Red River, Atchafalaya & Bayou Boeuf Levee District reserves the right to reject any and all bids or to accept any bid(s), which in the opinion of the Levee District will be in the best interest of the District.

Please contact Ryan Ingles or Ellen Burke at 318-443-9646 or [www.rrabb.net](http://www.rrabb.net) for bid sheet and/or for additional information.

Published: The Alexandria Town Talk  
Wednesday, February 12, 2025  
Wednesday, February 19, 2025  
Wednesday, February 26, 2025

# BID SPECIFICATIONS

Scope: It is the intent of these specifications to describe the minimum requirements for two new tandem diesel trucks with 12-14 cubic yard dump bed.

Unless otherwise stated, the use of manufacturers name and product numbers are for descriptive purposes and to establish general quality levels only, they are not intended to be restrictive.

The equipment bid will be evaluated based on specifications, cost, delivery schedule, warranty, availability of parts and service and its capability to meet the needs of the Levee District.

The bidder shall represent by his bid that all equipment bid is new and unused. Bidder shall furnish a complete operator's manual.

It is required that the unit, as specified herein, shall be completely assembled and ready for operation.

## 1. **Intent:**

It is the intent of this specification to provide for the purchase and delivery of two new tandem diesel trucks with 12-14 cubic yard dump bed, as per specifications.

## 2. **General:**

These specifications describe the minimum requirements for the dump trucks. This equipment shall be new, or current manufacture, and must meet all State and Federal safety standards in effect at time of delivery. Any additions, deletions, or variations from the following specifications must be noted. Any items, appearing in the manufacturer's regular published specifications furnished by the Bidder are assumed to be included in the "Bidders Proposal." Any additions, deletions, or variations from the manufacturer's regular published specification must be outlined in an attached letter. Minor deviations from this specification which do not impair comparative functional equivalency will be accepted.

## 3. **Workmanship:**

Any unit delivered under this specification is subject to rejection if there is evidence of poor workmanship, by either the vendor or the original manufacturer. Any defect, so noted, may be corrected by the vendor to the satisfaction of the Levee District and must be completed before invoices can be processed for payment.

## 4. **Typical Specifications:**

International 2026 HV607 SBA (HV607) with 12-14 Cubic Yard Warren Dump Body specifications were used to develop these specifications. Machines of similar style, type, character, quality, and purpose conforming to the detailed requirements listed below will be considered equivalent.

## 5. **Warranty:**

Vendors statement of warrantee shall be submitted as part of the bid. Base coverage shall be for 12 months, unlimited miles, unlimited hours. Engine coverage shall be for 72 months or 150,000 miles (whichever occurs first). Axle coverage shall be for 24 months, unlimited miles, unlimited hours. Cab Structure/Corrosion shall be for 60 months, unlimited miles, unlimited hours.

6. **Training:**

The successful bidder is to instruct appropriate personnel on the operation and proper maintenance of the units as part of the bid at no additional cost.

7. **Parts:**

Bidder must show conclusive evidence of adequate parts and service available within the Levee District region.

8. **Literature:**

One (1) operators manual per machine, certificate of origin, sales invoice, warrantee agreement, and dealer's service policy properly executed, to be furnished at time of delivery.

## Technical Specifications

<b>AXLE CONFIG:</b>	6X4
<b>APPLICATION:</b>	Construction Dump
<b>MISSION:</b>	Requested GVWR: 52000. Calc. GVWR: 52000. Calc. GCWR: 80000 Calc. Start / Grade Ability: 21.68% / 2.19% @ 55 MPH Calc. Geared Speed: 77.1 MPH
<b>DIMENSION:</b>	Wheelbase: 171.00, CA: 103.90, Axle to Frame: 63.00
<b>ENGINE, DIESEL:</b>	{Cummins L9 350} EPA 2024, 350HP @ 2200 RPM, 1050 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)
<b>TRANSMISSION, AUTOMATIC:</b>	{Allison 3000 RDS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway
<b>CLUTCH:</b>	Omit Item (Clutch & Control)
<b>AXLE, FRONT NON-DRIVING:</b>	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
<b>AXLE, REAR, TANDEM:</b>	{Meritor MT-40-14X-4DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, .433"(11mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends Gear Ratio: 5.29
<b>CAB:</b>	Conventional, Day Cab
<b>TIRE, FRONT:</b>	(2) 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
<b>TIRE, REAR:</b>	(8) 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive
<b>SUSPENSION, REAR, TANDEM:</b>	{Hendrickson RT-403} Walking Beam, 40,000-lb Capacity, 52" Axle Spacing, Multileaf Springs, with Rubber Center Bushings
<b>PAINT:</b>	Cab schematic 100WL Location 1: 9219, Winter White (Std) Chassis schematic N/A

## **AXLE CONFIGURATION**

---

AXLE CONFIGURATION 6x4

### Notes

: Pricing may change if axle configuration is changed.

## **ENGINE**

---

ENGINE, DIESEL {Cummins L9 350} EPA 2024, 350HP @ 2200 RPM, 1050 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)

EMISSION, CALENDAR YEAR {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2025

CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty

CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Door

VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA/MA/OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle.

### Notes

: CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.

RADIATOR Aluminum, Cross Flow, Front to Back System, 1469 SqiIn, with 1172 SqiIn Charge Air Cooler

### Includes

: DEAERATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

: RADIATOR HOSES Premium, Rubber

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

### Includes

: FAN Nylon

AIR CLEANER Dual Element

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

ENGINE CONTROL, REMOTE MOUNTED No Provision for Remote Mounted Engine Control

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

## **TRANSMISSION**

---

TRANSMISSION, AUTOMATIC {Allison 3000 RDS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

OIL COOLER, TRANSMISSION {Modine} Water to Oil Type

PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission

## **CLUTCH**

---

CLUTCH Omit Item (Clutch & Control)

## **REAR AXLES, SUSPENSIONS**

---

AXLE, REAR, TANDEM {Meritor MT-40-14X-4DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, .433"(11mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends . Gear Ratio: 5.29

SUSPENSION, REAR, TANDEM {Hendrickson RT-403} Walking Beam, 40,000-lb Capacity, 52" Axle Spacing, Multileaf Springs, with Rubber Center Bushings

## **FRONT AXLES**

---

AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity

## **FRONT SUSPENSIONS**

---

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity, with Shock Absorbers

## **CABS, COWLS, BODIES**

---

CAB Conventional, Day Cab

ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab

AIR CONDITIONER with Integral Heater and Defroster

CAB INTERIOR TRIM Classic, for Day Cab

### Includes

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger

: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted

: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap

CAB MOUNTING HEIGHT EFFECTS High Cab in Lieu of Mid High Cab Mounting (Approx. 4.5")

CAB REAR SUSPENSION Air Bag Type

GAUGE CLUSTER Base Level; English with English Electronic Speedometer

### Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for

: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)

GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster

INSTRUMENT PANEL Flat Panel

IP CLUSTER DISPLAY Omit Display of Fault Codes in Instrument Cluster and Disable Blink Codes, Requires Service Tool to Retrieve and View Fault Code

MIRRORS (2) C-Loop, Heated, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width

### Notes

: Mirror Dimensions are Rounded to the Nearest 0.5"

MONITOR, TIRE PRESSURE Omit

SEAT, DRIVER {National 2000 195} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2

Position Front Cushion Adjust, 6-23 Degree Angle Back Adjust

SEAT, PASSENGER {National} Non Suspension, High Back, Fixed Back, Integral Headrest, Vinyl

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

## **FRAMES**

---

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.437" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL

BUMPER, FRONT Swept Back, Steel, Heavy Duty

TOW HOOK, FRONT (2) Frame Mounted

WHEELBASE RANGE 169" (430cm) Through and Including 219" (555cm)

PINTLE HOOK (HITCH), heavy-duty, with glad hands, mounted at rear of frame with hand control valve with tractor protection valve, for straight truck.

## **BRAKES**

---

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

### Includes

: BRAKE LINES Color and Size Coded Nylon

: DRAIN VALVE Twist-Type

: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System

BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity

BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn

SLACK ADJUSTERS, FRONT {Haldex} Automatic

BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake

SLACK ADJUSTERS, REAR {Haldex} Automatic

PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type

AIR COMPRESSOR {Cummins} 18.7 CFM

AIR DRYER {Bendix AD-9} with Heater

AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab

AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Back of Cab, Perpendicular to Rail

DRAIN VALVE (3) with Pull Chains for Air Tanks

TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck

Notes

: When electronic stability control is ordered with trailer connections on a 4x2 truck, please check the operator manual for trailer weight restrictions.

**STEERING**

---

STEERING GEAR {Sheppard M100} Power

STEERING COLUMN Tilting

STEERING WHEEL 4-Spoke; 18" Dia., Black

**DRIVELINES**

---

DRIVELINE SYSTEM {Dana Spicer} 1710 Main Driveline with 1710 Interaxle Shaft, for 6x4

**EXHAUST SYSTEMS**

---

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab

AFTERTREATMENT COVER Steel, Black

ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

EXHAUST HEIGHT 8' 10"

MUFFLER/TAIL PIPE GUARD (1) Aluminum

TAIL PIPE (1) Turnback Type

**ELECTRICAL SYSTEMS**

---

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

- : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
- : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
- : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
- : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
- : STARTER SWITCH Electric, Key Operated
- : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
- : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
- : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
- : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
- : WIRING, CHASSIS Color Coded and Continuously Numbered

ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with Remote Sense

ANTENNA Shark Fin, Roof Mounted

BACK-UP ALARM Electric, 102 dBA

BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab

BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade



CRUISE DISABLED W/WIPERS Cruise Control will Automatically be Disabled if Windshield Wipers are Turned on when Vehicle Speed Exceeds 25 MPH

FOG LIGHTS (2) Clear Lens, LED, Rectangular, with White Light Source

HEADLIGHTS Halogen

HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord

HORN, ELECTRIC Disc Style

INDICATOR, LOW COOLANT LEVEL with Audible Alarm

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

SPEAKERS (2) 6.5" Dual Cone Mounted in Doors

STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

TRAILER CONNECTION SOCKET {Erich Jaeger} 7-Way, Mounted at Rear of Frame, Wired for Turn Signals Independent of Stop, Compatible with Trailers with Combined Stop, Tail, Turn Lamps

TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

## **FRONT END**

---

FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV

BUG SCREEN Mounted Behind Grille

GRILLE Stationary, Chrome

LOGOS EXTERIOR Model Badges, Shipped Loose, Located in Cab

LOGOS EXTERIOR, ENGINE Badge Shipped Loose

QUARTER FENDERS for Rear Wheels, Black Plastic; Frame Mounted

## **SPEEDOMETER, TOOLS, MISC**

---

COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360

PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "WL"

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

SPECIAL RATING, GVWR Limited to 68,000-lb GVWR

## **FUEL TANKS**

---

FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 70 US Gal (265L), Mounted Left Side, Under Cab

DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab

FUEL/WATER SEPARATOR {Racor 400 Series} with Primer Pump, Includes Water-in-Fuel Sensor, Mounted on Engine

## **WHEELS, TIRES - FRONT**

---

WHEELS, FRONT {Maxion 91541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(2) TIRE, FRONT 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position

**WHEELS, TIRES - REAR**

---

WHEELS, REAR {Maxion 91541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(8) TIRE, REAR 11R22.5 Load Range G DH37 (HANKOOK), 498 rev/mile, 75 MPH, Drive

**WHEELS MISC OPTIONS**

---

PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint

PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint

**Services Section:**

**DUMP BED**

---

12-14yd Warren Dump Body, electric tarp system, metal side boards, asphalt apron, air tail gate, installed.

List Deviations from Specs:

1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

4. \_\_\_\_\_

5. \_\_\_\_\_

6. \_\_\_\_\_

7. \_\_\_\_\_

8. \_\_\_\_\_

9. \_\_\_\_\_

10. \_\_\_\_\_

11. \_\_\_\_\_

12. \_\_\_\_\_

13. \_\_\_\_\_

14. \_\_\_\_\_

15. \_\_\_\_\_

16. \_\_\_\_\_

# PRICE PROPOSAL

In compliance with your invitation for bids for the furnishing of

## **TWO (2) NEW Tandem Diesel Trucks with 12-14 Cubic Yard Dump Bed**

And having examined the specifications with related documents and being familiar with all of the conditions surrounding the availability of materials and labor, the bidder hereby proposes to furnish the equipment called for in accordance with the contract documents, within the time set forth therein, and at the price stated below. This price is to cover all expenses incurred in supplying the equipment required under the contract documents, of which this proposal is a part.

Furnish and deliver to Red River, Atchafalaya & Bayou Bouef Levee District, 10 Calvert Drive, Alexandria, Louisiana 71303, two dump trucks, as specified herein, for the following price, **EXCLUDING SALES TAX.**

\_\_\_\_\_ \$ \_\_\_\_\_  
Words Figures

Delivery Period: \_\_\_\_\_ months

The above lump sum prices shall include all transportation, labor, overhead, profit, applicable taxes, insurance, etc. to cover the supplying of the equipment called for.

The bidder agrees that this proposal shall be good and may not be withdrawn for a period of 30 calendar days after the scheduled closing time for receiving proposals.

Submitted by:

\_\_\_\_\_  
Name of Person, Firm or Corporation

By: \_\_\_\_\_  
Signature and Title

\_\_\_\_\_  
Business Address

\_\_\_\_\_  
Phone Number

**\*\*\*Detailed specifications shall be included in bid proposal as attached documentation.\*\*\***